




	Impulse	400 KL		300 KL		XL KL	
Chassis							
4-wheel central brake with straight run function		•		•		•	
100 mm double caster		◦		◦		x	
125 mm caster		◦		◦		◦	
150 mm double caster		•		•		•	
Comfort characteristics							
Comfort seat		•		•		•	
Auto-contour		•		•		•	
Mobilisation							
Automatic CPR system		•		•		•	
Anti-Trendelenburg positioning		•		•		•	
Trendelenburg positioning (shock position)		•		•		•	
Removable bed fronts with fast locking system		•		•		•	
Side rail							
Mattress holder without side rail		◦		◦		◦	
Mobilising side rail system		•		•		•	
Safety							
Low-level bed – Fall prevention		•		x		x	
Extension possibilities							
Integrated bed extension		•		•		•	
Bedding storage (only in conjunction with integr. bed extension)		◦		◦		◦	
Mattress base		90 cm	80 cm	90 cm	80 cm	100 cm	120 cm
Metal rail		◦	◦	◦	◦	•	◦
Comfort		◦	◦	◦	◦	x	x
ABS		•	◦	•	◦	x	x
Technical data							
Working position		83 cm		86 cm		86 cm	
Low position		30 cm		36 cm		36 cm	
Safe working load		250 kg		250 kg		300 kg	
External dimensions		106 x 220 cm		106 x 220 cm		116 x 206 cm	
Mattress base		90 x 200 cm		90 x 200 cm		100 x 200 cm	
Adjustment functions							

• as standard ◦ optional x not available



SAFETY IN THE IMPULSE SERIES

EC Medical Device Directive
93/42 EEC

Adjustable care beds
DIN EN 1970 / DIN EN 60601-2-52:2010

Medical electrical equipment
DIN EN 60601-1

Electromagnetic compatibility
DIN EN 60601-1-2